



## China 608rs Bearing Supplier



6000 Bearing 2D drawings and 3D CAD models

NSK motor bearing 6000 6000ZZ 6000ZZCM  
deep groove ball bearing

Bearing No. 6000

Size	10x26x8 mm
Bore Diameter	10 mm
Outer Diameter	26 mm
Width	8 mm
d	10 mm
D	26 mm
B	8 mm
C	8 mm
r min.	0,3 mm
da min.	12 mm
da max	13 mm
Da max.	24 mm
ra max.	0,3 mm
Weight	0,018 Kg
Basic dynamic load rating (C)	4,55 kN
Basic static load rating (C0)	1,97 kN
(Grease) Lubrication Speed	30 000 r/min
(Oil) Lubrication Speed	36 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	0029176012167
Product Group	B00308



## China 608rs Bearing Supplier

Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Item Number	6000
Weight / LBS	0.019
Bore	0.394 Inch   10 Millimeter
Outer Race Width	0.315 Inch   8 Millimeter
Outside Diameter	1.024 Inch   26 Millimeter
bore diameter:	10 mm
closure type:	Open
outside diameter:	26 mm
internal clearance:	Normal Clearance
overall width:	8 mm
manufacturer upc number:	029176012167



## China 608rs Bearing Supplier

bore type:	Round
SRI	2.46
hidYobi	6000
LangID	1
D_	26
SREX	0.015
B_	8
da min	12
hidTable	ecat_NSRDGB
Oil rpm	36000
SRE	2.67
mass	0.018
GRS rpm	30000
ra	0.3
SRIX	0.015
D_a	24
SRIN	-0.015
C0	1.97
fo	12.4
SREN	-0.015
DE_	22.762
Prod_Type3	DGBB_SR_OT
DA_	4.762
bomp	0
Z_	7
yobi	6000
C_conv	4550
ALPHA_	0
SDM_	18
r	0.3
KBRG	6101
SBRG	10



## China 608rs Bearing Supplier

DI_	13.238
-----	--------